



**HEAVY-DUTY  
WATERPROOFING  
SEALANT**

**PU-100**

**FORTRESS Heavy-Duty Waterproofing Sealant** is a polyurethane modified heavy duty waterproofing sealant that prevents moisture ingression to applied surfaces. It can be applied to seal all visible cracks, gaps, joint areas and overlaps. With its superior durability, flexibility and elongation, **FORTRESS Heavy-Duty Waterproofing Sealant** can be left exposed to extreme weather conditions without any degradation to its waterproofing performance.

## COMPOSITION

Polyurethane Hybrid  
Calcium Carbonate  
Water

## SURFACE PREPARATION

Surface must be clean, dry, stable and free from dirt, dust, oil, grease, mildew and other contaminants that will impede on the proper adhesion of the coating.

**Previously Caulked Surfaces:** It is critical to remove as much old sealant as possible before applying new sealant, especially if it is cracked, eroded or pulled away from the joint.

**Mildewed Surfaces:** Any existing mildew on the surface must be completely killed and removed prior to the application of new sealant.

## FEATURES AND BENEFITS

- Resistant to Tearing
- Excellent Adhesion to Most Surfaces
- Outstanding Waterproofing Protection on Applied Areas
- Ability to Withstand Extreme Weather Conditions
- Paintable with any Water-based Paint
- Water-based, Low VOC and Non-corrosive
- Ready and Easy to Apply

## APPLICATIONS

- Visible Cracks
- Gaps
- Joint Areas
- Tek Screws
- Overlaps on different types of substrates such as: Metal, Concrete, Wood, Gypsum Boards and Fiber Cement Boards





**COLOR:** Gray

**PACKAGING:** 1 liters, 4 liters

**PACKAGING:** 1.5Kg (Approx.)

**COVERAGE:** 1 liter - 10 linear meters  
@ 1cm x 1cm thickness

**DRYING TIME:** Wait 24 hours before painting with water-based paint.

